

TICKOPUR R 60

Revision date: 01.03.2018

No: 83028

Page 1 of 8

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

TICKOPUR R 60

1.2. Relevant identified uses of the substance or mixture and uses advised against**Use of the substance/mixture**

Cleaning agent. Intensive cleaner for the ultrasonic bath, concentrate.

Restricted to professional users.

1.3. Details of the supplier of the safety data sheet

Company name: DR.H.STAMM GmbH Chemische Fabrik
Street: Heinrichstr. 3 – 4
Place: 12207 Berlin, GERMANY
Telephone: +49 30 76880-280
e-mail: info@dr-stamm.de
Internet: www.dr-stamm.de
Responsible Department: sdb@dr-stamm.de, Tel.: +49 30 76880-258

1.4. Emergency telephone number: 24-hours-emergency: Giftnotruf Berlin: +49 30 30686700 (german, english)

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****Regulation (EC) No. 1272/2008**

Hazard categories:

Skin corrosion/irritation: Skin Corr. 1A

Serious eye damage/eye irritation: Eye Dam. 1

Hazard Statements:

Causes severe skin burns and eye damage.

Causes serious eye damage.

2.2. Label elements**Regulation (EC) No. 1272/2008****Hazard components for labelling**

Sodium hydroxide; caustic soda

Signal word: Danger**Pictograms:****Hazard statements**

H314 Causes severe skin burns and eye damage.

Precautionary statements

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

SECTION 3: Composition/information on ingredients**3.2. Mixtures**

TICKOPUR R 60

Revision date: 01.03.2018

No: 83028

Page 2 of 8

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification according to Regulation (EC) No. 1272/2008 [CLP]			
7732-18-5	Water			80-90 %
	213-791-2			
1310-73-2	Sodium hydroxide; caustic soda			<12,5 %
	215-185-5	011-002-00-6	01-2119457892-27	
	Skin Corr. 1A; H314			
527-07-1	Sodium gluconate			<5,0 %
	208-407-7		*1	
100085-64-1	Cocobetainamido Amphopropionate			<1,0 %
	309-206-8		*	
	Skin Irrit. 2, Eye Irrit. 2, Aquatic Acute 1; H315 H319 H400			

Full text of H and EUH statements: see section 16.

Further Information

*Polymer

*1 Exempted from registration (Annex IV listed)

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Take off immediately all contaminated clothing.

After inhalation

In case of inhalation of aerosols/spray mist/splash spots: Consult physician. Provide fresh air.

After contact with skin

After contact with skin, wash immediately with: Water and soap. In case of skin irritation, seek medical treatment.

After contact with eyes

Immediately flush eyes with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Consult an ophthalmologist.

After ingestion

Rinse mouth immediately and drink large quantities of water. Do not induce vomiting. Consult physician.

4.2. Most important symptoms and effects, both acute and delayed

No symptoms known up to now.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Water. Foam. Atomized water.

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

Can be released in case of fire: Nitrogen oxides (NOx). Carbon dioxide (CO2).

TICKOPUR R 60

Revision date: 01.03.2018

No: 83028

Page 3 of 8

5.3. Advice for firefighters

Special protective equipment for fire-fighters: Use appropriate respiratory protection. In case of fire and/or explosion do not breathe fumes.

Additional information

Material is not combustible. Extinguishing materials should be selected according to the surrounding area.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Keep away from unprotected people. Keep upwind. Wear respiratory protection when in the presence of vapour, dust, and aerosols. Guide people to safety.

6.2. Environmental precautions

Do not empty into drains or the aquatic environment. Prevent spreading over great surfaces (e.g. by damming or installing oil booms).

6.3. Methods and material for containment and cleaning up

Clean contaminated articles and floor according to the environmental legislation. Treat the assimilated material according to the section on waste disposal. Suitable absorbing material: Sand Universal binding agent. earth. Sawdust.

6.4. Reference to other sections

See protective measures under point 7 and 8.

SECTION 7: Handling and storage**7.1. Precautions for safe handling****Advice on safe handling**

It is recommended to organise all working processes in order to exclude the following: skin contact. Eye contact.

Advice on protection against fire and explosion

Product is not: Oxidizing. Flammable. Explosive.

7.2. Conditions for safe storage, including any incompatibilities**Requirements for storage rooms and vessels**

Store only in original container.
Keep away from food, drink and animal feedingstuffs.

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****Occupational exposure limits**

CAS No	Substance	ppm	mg/m ³	fib/cm ³	Category	Origin
1310-73-2	Sodium hydroxide	-	-		TWA (8 h)	
		-	2		STEL (15 min)	

DNEL/DMEL values

CAS No	Substance	Exposure route	Effect	Value
1310-73-2	Sodium hydroxide; caustic soda			
	Worker DNEL, long-term	inhalation	local	1 mg/m ³
	Consumer DNEL, long-term	inhalation	local	1 mg/m ³

8.2. Exposure controls**Appropriate engineering controls**

Refer to chapter 7. No further action is necessary.

TICKOPUR R 60

Revision date: 01.03.2018

No: 83028

Page 4 of 8

Protective and hygiene measures

Do not eat, drink, smoke or sneeze at the workplace.
Take off immediately all contaminated clothing.
Wash hands before breaks and at the end of work.

Eye/face protection

Tightly sealed safety glasses.

Hand protection

Suitable material: PE (polyethylene). CR (polychloroprenes, Chloroprene rubber). NBR (Nitrile rubber). Butyl rubber. FKM (Fluoroelastomer (Viton)).
penetration time (maximum wearing period): >480 min. Breakthrough times and swelling characteristics of the material must be taken into consideration.
Recommended protective gloves brand: Camapren 722, Manufacturer: KCL, or comparable makes from other companies.

Skin protection

Lab apron.

Respiratory protection

Respiratory protection not required.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Physical state:	liquid
Colour:	clear, light yellow
Odour:	characteristic

pH-Value (at 20 °C):

13,6 (conc.) 12,3 (1 %) DGF H-III 1

Test method**Changes in the physical state**

Melting point:	-15 °C
Initial boiling point and boiling range:	100 °C
Sublimation point:	n.a.
Softening point:	n.a.
Flash point:	non-flammable

Explosive properties

not Explosive.

Oxidizing properties

not oxidizing.

Density (at 20 °C):

1,158 g/cm³ DIN 12791

Water solubility:
(at 20 °C)

complete miscible

SECTION 10: Stability and reactivity**10.1. Reactivity**

Exothermic reactions with: acid, concentrated.

10.2. Chemical stability

The product is chemically stable under normal ambient conditions.

10.3. Possibility of hazardous reactions

None, in case of proper use.

10.5. Incompatible materials

acid, concentrated. Reducing agents.

TICKOPUR R 60

Revision date: 01.03.2018

No: 83028

Page 5 of 8

10.6. Hazardous decomposition products

None, in case of proper use.

Further information

Do not mix with other products.

SECTION 11: Toxicological information**11.1. Information on toxicological effects****Acute toxicity**

Based on available data, the classification criteria are not met.

CAS No	Chemical name					
	Exposure route	Dose	Species	Source	Method	
1310-73-2	Sodium hydroxide; caustic soda					
	oral	LD50 mg/kg	2000	rat		
100085-64-1	Cocobetainamido Amphopropionate					
	oral	LD50 mg/kg	>2000	Ratte	OECD 401	
	dermal	LD50 mg/kg	>2000	Ratte	OECD 402	

Irritation and corrosivity

Causes severe skin burns and eye damage.

Irritant effect on the skin: corrosive. Irritant effect on the eye: corrosive.

Sensitising effects

Based on available data, the classification criteria are not met.

no danger of sensitization.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

SECTION 12: Ecological information**12.1. Toxicity**

Technically correct releases of minimal concentrations to adapted biological sewage treatment facility, will not disturb the biodegradability of activated sludge. due to the alkaline character of the product, usually, it has to be neutralized before contaminated effluents are introduced into the waste water treatment system.

TICKOPUR R 60

Revision date: 01.03.2018

No: 83028

Page 6 of 8

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
1310-73-2	Sodium hydroxide; caustic soda					
	Acute fish toxicity	LC50	125 mg/l	96 h	Gambusia affinis	SDB Lieferant
	Acute crustacea toxicity	EC50	40,4 mg/l	48 h	Ceriodaphnia	ECHA
100085-64-1	Cocobetainamido Amphopropionate					
	Acute fish toxicity	LC50	15 mg/l	96 h	Regenbogenforelle	OECD 203
	Acute algae toxicity	ErC50	0,15 mg/l	72 h	Selenastrum capricornutum	OECD 201
	Acute crustacea toxicity	EC50	4,4 mg/l	48 h	Daphnia magna	OECD 202
	Acute bacteria toxicity	>100 mg/l			Belebtschlamm	OECD 209

12.2. Persistence and degradability

The surfactants contained in this preparation comply with the biodegradability criteria as laid down in Regulation (EC) No.648/2004 on detergents. Data to support this assertion are held at the disposal of the competent authorities of the Member States and will be made available to them, at their direct request or at the request of a detergent manufacturer.

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
100085-64-1	Cocobetainamido Amphopropionate			
	OECD 301A	>70 %	28	
	easily biodegradable			

12.3. Bioaccumulative potential

On the basis of existing data about disposal/decomposition and bio-accumulation potential, long term environmental damage is unlikely.

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

not applicable

12.6. Other adverse effects

No data available

SECTION 13: Disposal considerations**13.1. Waste treatment methods****Advice on disposal**

According to EAKV, allocation of waste identity numbers/waste descriptions must be carried out in a specific way for every industry and process.

Waste disposal number of waste from residues/unused products

200129 MUNICIPAL WASTES (HOUSEHOLD WASTE AND SIMILAR COMMERCIAL, INDUSTRIAL AND INSTITUTIONAL WASTES) INCLUDING SEPARATELY COLLECTED FRACTIONS; separately collected fractions (except 15 01); detergents containing hazardous substances; hazardous waste

Waste disposal number of used product

200129 MUNICIPAL WASTES (HOUSEHOLD WASTE AND SIMILAR COMMERCIAL, INDUSTRIAL AND INSTITUTIONAL WASTES) INCLUDING SEPARATELY COLLECTED FRACTIONS; separately collected fractions (except 15 01); detergents containing hazardous substances; hazardous waste

Contaminated packaging

Completely emptied packings can be re-cycled.

TICKOPUR R 60

Revision date: 01.03.2018

No: 83028

Page 7 of 8

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number:	UN1824
14.2. UN proper shipping name:	SODIUM HYDROXIDE, SOLUTION
14.3. Transport hazard class(es):	8
14.4. Packing group:	II
Hazard label:	8
Classification code:	C5
Limited quantity:	1 L
Transport category:	2
Hazard No:	80
Tunnel restriction code:	E

Other applicable information (land transport)

Excepted Quantity: E2

Marine transport (IMDG)

14.1. UN number:	UN1824
14.2. UN proper shipping name:	SODIUM HYDROXIDE SOLUTION
14.3. Transport hazard class(es):	8
14.4. Packing group:	II
Hazard label:	8
Marine pollutant:	no
Special Provisions:	-
Limited quantity:	1 L
EmS:	F-A, S-B

Other applicable information (marine transport)

Excepted Quantity: E2

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number:	UN1824
14.2. UN proper shipping name:	SODIUM HYDROXIDE SOLUTION
14.3. Transport hazard class(es):	8
14.4. Packing group:	II
Hazard label:	8
Special Provisions:	A3 A803
Limited quantity Passenger:	0.5 L
IATA-packing instructions - Passenger:	851
IATA-max. quantity - Passenger:	1 L
IATA-packing instructions - Cargo:	855
IATA-max. quantity - Cargo:	30 L

Other applicable information (air transport)

Excepted Quantity: E2

Passenger-LQ: Y840

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**EU regulatory information**

2004/42/EC (VOC): 0 % (0 g/l)

National regulatory information

Water contaminating class (D): 1 - slightly water contaminating

TICKOPUR R 60

Revision date: 01.03.2018

No: 83028

Page 8 of 8

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information**Changes**

Data changed from previous versions: 2.1., 3.2., 8.1., 9.1., 11.1., 12.1., 12.2., 13.1., 15.1., 16.

Classification for mixtures and used evaluation method according to Regulation (EC) No. 1272/2008 [CLP]

Classification	Classification procedure
Skin Corr. 1A; H314	Calculation method
Eye Dam. 1; H318	Calculation method

Relevant H and EUH statements (number and full text)

H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H400	Very toxic to aquatic life.

Further Information

Training instructions: Notice the directions for use on the label.

The information is based on present level of our knowledge. It does not, however, give assurances of product properties and establishes no contract legal rights.

Identified uses

No	Short title	LCS	SU	PC	PROC	ERC	AC	TF	Specification
1	TICKOPUR R 60	IS, PW	0	35	8a, 9, 13	8a	0	26	

LCS: Life cycle stages

PC: Product categories

ERC: Environmental release categories

TF: Technical functions

SU: Sectors of use

PROC: Process categories

AC: Article categories

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)