

STAMMOPUR R

Revision date: 21.02.2018

No: 83007

Page 1 of 9

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

STAMMOPUR R

1.2. Relevant identified uses of the substance or mixture and uses advised against**Use of the substance/mixture**

Cleaning agent. Instrument cleaner for the ultrasonic bath, concentrate.

Restricted to professional users.

1.3. Details of the supplier of the safety data sheet

Company name: DR.H.STAMM GmbH Chemische Fabrik
Street: Heinrichstr. 3 – 4
Place: 12207 Berlin, GERMANY
Telephone: +49 30 76880-280
e-mail: info@dr-stamm.de
Internet: www.dr-stamm.de
Responsible Department: sdb@dr-stamm.de, Tel.: +49 30 76880-258

1.4. Emergency telephone number: 24-hours-emergency: Giftnotruf Berlin: +49 30 30686700 (german, english)

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****Regulation (EC) No. 1272/2008**

Hazard categories:

Serious eye damage/eye irritation: Eye Dam. 1

Hazard Statements:

Causes serious eye damage.

2.2. Label elements**Regulation (EC) No. 1272/2008****Hazard components for labelling**

Sulfonic acids, C14-17-sec-alkane, sodium salts

Signal word: Danger**Pictograms:****Hazard statements**

H318 Causes serious eye damage.

Precautionary statements

P280 Wear protective gloves/protective clothing/eye protection/face protection.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

SECTION 3: Composition/information on ingredients**3.2. Mixtures**

STAMMOPUR R

Revision date: 21.02.2018

No: 83007

Page 2 of 9

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification according to Regulation (EC) No. 1272/2008 [CLP]			
7732-18-5	Water			60-80 %
	213-791-2			
68920-66-1	C16-C18 Fatty alcohol, ethoxylated			<10,0 %
	-		*	
97489-15-1	Sulfonic acids, C14-17-sec-alkane, sodium salts			<7,5 %
	307-055-2		01-2119489924-20	
	Acute Tox. 4, Skin Irrit. 2, Eye Dam. 1, Aquatic Chronic 3; H302 H315 H318 H412			
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol			<5,0 %
	200-661-7	603-117-00-0	01-2119457558-25	
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336			
51981-21-6	N,N-bis(carboxylatomethyl)-L-glutamate, Sodium salt			<5,0 %
	257-573-7		01-2119493601-38	
95-14-7	1,2,3-Benzotriazole			<3,0 %
	202-394-1		01-2119979079-20	
	Acute Tox. 4, Eye Irrit. 2, Aquatic Chronic 2; H302 H319 H411			

Full text of H and EUH statements: see section 16.

Further Information

*Polymer

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Change contaminated clothing.

After inhalation

In case of inhaling spray mists, consult a doctor .

After contact with skin

After contact with skin, wash immediately with plenty of Water and soap.

After contact with eyes

Rinse immediately carefully and thoroughly with eye-bath or water. In case of troubles or persistent symptoms, consult an ophthalmologist.

After ingestion

Rinse mouth immediately and drink large quantities of water. Do not induce vomiting. Consult physician.

4.2. Most important symptoms and effects, both acute and delayed

No symptoms known up to now.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

STAMMOPUR R

Revision date: 21.02.2018

No: 83007

Page 3 of 9

Suitable extinguishing media

Water. Foam. Atomized water.

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

Can be released in case of fire: Nitrogen oxides (NOx). Carbon dioxide (CO2).

5.3. Advice for firefighters

Protective clothing.

Additional information

Material is not combustible. Extinguishing materials should be selected according to the surrounding area.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Wear personal protection equipment.

6.2. Environmental precautions

Do not empty into drains or the aquatic environment.

6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents).

Treat the assimilated material according to the section on waste disposal.

6.4. Reference to other sections

See protective measures under point 7 and 8.

SECTION 7: Handling and storage**7.1. Precautions for safe handling****Advice on safe handling**

No special technical protective measures are necessary.

Advice on protection against fire and explosion

Product is not: Oxidizing. Flammable. explosive.

7.2. Conditions for safe storage, including any incompatibilities**Requirements for storage rooms and vessels**

Store only in original container. Keep away from food, drink and animal feedingstuffs.

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****Occupational exposure limits**

CAS No	Substance	ppm	mg/m ³	fib/cm ³	Category	Origin
67-63-0	Isopropyl alcohol	200	-		TWA (8 h)	
		400	-		STEL (15 min)	

Biological limit values

CAS No	Substance	Parameter	Value	Test material	Sampling time
67-63-0	2-Propanol	Acetone	40 mg/L	Urine	End of shift at end of workweek

STAMMOPUR R

Revision date: 21.02.2018

No: 83007

Page 4 of 9

DNEL/DMEL values

CAS No	Substance	Exposure route	Effect	Value
97489-15-1	Sulfonic acids, C14-17-sec-alkane, sodium salts			
Worker DNEL, acute		dermal	local	2,8 mg/cm ²
Worker DNEL, long-term		dermal	systemic	5 mg/kg bw/day
Worker DNEL, long-term		inhalation	systemic	35 mg/m ³
Worker DNEL, long-term		dermal	local	2,8 mg/cm ²
Consumer DNEL, acute		dermal	local	2,8 mg/cm ²
Consumer DNEL, long-term		dermal	systemic	3,57 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	12,4 mg/m ³
Consumer DNEL, long-term		oral	systemic	7,1 mg/kg bw/day
Consumer DNEL, long-term		dermal	local	2,8 mg/cm ²
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol			
Consumer DNEL, long-term		oral	systemic	26 mg/kg bw/day
Worker DNEL, long-term		dermal	systemic	888 mg/kg bw/day
Consumer DNEL, long-term		dermal	systemic	319 mg/kg bw/day
Worker DNEL, long-term		inhalation	systemic	500 mg/m ³
Consumer DNEL, long-term		inhalation	systemic	89 mg/m ³

PNEC values

CAS No	Substance	Value
97489-15-1	Sulfonic acids, C14-17-sec-alkane, sodium salts	
Environmental compartment		
Freshwater		0,04 mg/l
Freshwater (intermittent releases)		0,06 mg/l
Marine water		0,004 mg/l
Freshwater sediment		9,4 mg/kg
Marine sediment		0,94 mg/kg
Soil		9,4 mg/kg
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol	
Freshwater		140,9 mg/l
Freshwater (intermittent releases)		140,9 mg/l
Marine water		140,9 mg/l
Freshwater sediment		552 mg/kg
Marine sediment		552 mg/kg
Soil		28 mg/kg

8.2. Exposure controls

Appropriate engineering controls

Refer to chapter 7. No further action is necessary.

Protective and hygiene measures

Do not eat, drink, smoke or sneeze at the workplace. Wash hands before breaks and at the end of work.

Eye/face protection

Wear eye/face protection.

STAMMOPUR R

Revision date: 21.02.2018

No: 83007

Page 5 of 9

Hand protection

Suitable material: PE (polyethylene). CR (polychloroprenes, Chloroprene rubber). NBR (Nitrile rubber). Butyl rubber. FKM (Fluoroelastomer (Viton)).

Tested protective gloves are to be worn: EN 374

Skin protection

Skin protection: not required.

Respiratory protection

Respiratory protection not required.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Physical state: liquid
Colour: clear, light yellow
Odour: characteristic

pH-Value (at 20 °C):

Test method
9,6 (1 %) DGF H-III 1

Changes in the physical state

Melting point: -8 °C
Initial boiling point and boiling range: >100 °C
Flash point: >65 °C

Explosive properties

not Explosive.

Oxidizing properties

not oxidizing.

Density (at 20 °C):

1,01 g/cm³ DIN 12791

Water solubility:

complete miscible

SECTION 10: Stability and reactivity**10.1. Reactivity**

None, in case of proper use.

10.2. Chemical stability

The product is chemically stable under normal ambient conditions.

10.3. Possibility of hazardous reactions

None, in case of proper use.

10.4. Conditions to avoid

Thermal decomposition can lead to the escape of irritating gases and vapors.

10.5. Incompatible materials

acid, concentrated.

10.6. Hazardous decomposition products

None, in case of proper use.

SECTION 11: Toxicological information**11.1. Information on toxicological effects****Acute toxicity**

Based on available data, the classification criteria are not met.

STAMMOPUR R

Revision date: 21.02.2018

No: 83007

Page 6 of 9

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
68920-66-1	C16-C18 Fatty alcohol, ethoxylated				
	oral	LD50 >2000 mg/kg	Ratte		
97489-15-1	Sulfonic acids, C14-17-sec-alkane, sodium salts				
	oral	LD50 500-2000 mg/kg	rat		OECD 401
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol				
	oral	LD50 4750 mg/kg	rat		OECD 401
	dermal	LD50 12800 mg/kg	kan		OECD 402
	inhalative (4 h) vapour	LC50 >25 mg/l	rat		OECD 403
51981-21-6	N,N-bis(carboxylatomethyl)-L-glutamate, Sodium salt				
	oral	LD50 >2000 mg/kg		EC B.1	
	dermal	LD50 >2000 mg/kg		OECD 402	
	inhalative (4 h) vapour	LC50 4,2 mg/l		OECD 403	
95-14-7	1,2,3-Benzotriazole				
	oral	ATE 500 mg/kg			

Irritation and corrosivity

Causes serious eye damage.

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Risk of serious damage to eyes.

Sensitising effects

Based on available data, the classification criteria are not met.

no danger of sensitization.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

SECTION 12: Ecological information**12.1. Toxicity**

Technically correct releases of minimal concentrations to adapted biological sewage treatment facility, will not disturb the biodegradability of activated sludge.

STAMMOPUR R

Revision date: 21.02.2018

No: 83007

Page 7 of 9

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
68920-66-1	C16-C18 Fatty alcohol, ethoxylated					
	Acute fish toxicity	LC50 30 mg/l	96 h			
	Acute crustacea toxicity	EC50 >1000 mg/l	48 h			
97489-15-1	Sulfonic acids, C14-17-sec-alkane, sodium salts					
	Acute fish toxicity	LC50 1-10 mg/l	96 h	Danio rerio		OECD 203
	Acute algae toxicity	ErC50 >61 mg/l	72 h	Desmodesmus subspicatus		OECD 201
	Acute crustacea toxicity	EC50 9,81 mg/l	48 h	Daphnia magna		OECD 202
	Fish toxicity	NOEC 0,85 mg/l	28 d	Oncorhynchus mykiss		OECD 204
	Crustacea toxicity	NOEC 0,36 mg/l	22 d	Daphnia magna		OECD 202
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol					
	Acute fish toxicity	LC50 >100 mg/l	96 h			
	Acute bacteria toxicity	(>100 mg/l)				
51981-21-6	N,N-bis(carboxylatomethyl)-L-glutamate, Sodium salt					
	Acute fish toxicity	LC50 >100 mg/l	96 h	Oncorhynchus mykiss	OECD 203	
	Acute algae toxicity	ErC50 >100 mg/l	72 h	Desmodesmus subspicatus	OECD 201	
	Acute crustacea toxicity	EC50 >100 mg/l	48 h	Daphnien	OECD 202	
	Acute bacteria toxicity	--- g O2/g (--- mg/l)			OECD 209	

12.2. Persistence and degradability

The surfactants contained in this preparation comply with the biodegradability criteria as laid down in Regulation (EC) No.648/2004 on detergents. Data to support this assertion are held at the disposal of the competent authorities of the Member States and will be made available to them, at their direct request or at the request of a detergent manufacturer.

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
68920-66-1	C16-C18 Fatty alcohol, ethoxylated			
	OECD 301D	>70 %	28	
	Leicht biologisch abbaubar			
97489-15-1	Sulfonic acids, C14-17-sec-alkane, sodium salts			
	OECD 301 B	78 %	28	
	leicht biologisch abbaubar			
	OECD 301 E	98 %	28	
	leicht biologisch abbaubar			
	OECD 303 A	96,2 %	34	
	leicht biologisch abbaubar			

12.3. Bioaccumulative potential

On the basis of existing data about disposal/decomposition and bio-accumulation potential, long term environmental damage is unlikely.

STAMMOPUR R

Revision date: 21.02.2018

No: 83007

Page 8 of 9

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
51981-21-6	N,N-bis(carboxylatomethyl)-L-glutamate, Sodium salt	<0

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

not applicable

12.6. Other adverse effects

No data available

SECTION 13: Disposal considerations**13.1. Waste treatment methods****Advice on disposal**

According to EAKV, allocation of waste identity numbers/waste descriptions must be carried out in a specific way for every industry and process.

Waste disposal number of waste from residues/unused products

200129 MUNICIPAL WASTES (HOUSEHOLD WASTE AND SIMILAR COMMERCIAL, INDUSTRIAL AND INSTITUTIONAL WASTES) INCLUDING SEPARATELY COLLECTED FRACTIONS; separately collected fractions (except 15 01); detergents containing hazardous substances; hazardous waste

Waste disposal number of used product

180106 WASTES FROM HUMAN OR ANIMAL HEALTH CARE AND/OR RELATED RESEARCH (EXCEPT KITCHEN AND RESTAURANT WASTES NOT ARISING FROM IMMEDIATE HEALTH CARE); wastes from natal care, diagnosis, treatment or prevention of disease in humans; chemicals consisting of or containing hazardous substances; hazardous waste

Contaminated packaging

Completely emptied packings can be re-cycled.

SECTION 14: Transport information**Other applicable information**

Not a hazardous material with respect to transportation regulations.

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

2004/42/EC (VOC): 4,9 % (49,49 g/l)

National regulatory information

Water contaminating class (D): 2 - clearly water contaminating

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information**Changes**

Data changed from previous versions: 2.1., 3.2., 8.1., 9.1., 11.1., 12.1., 12.2., 13.1., 16.

Classification for mixtures and used evaluation method according to Regulation (EC) No. 1272/2008 [CLP]

Classification	Classification procedure
Eye Dam. 1; H318	Calculation method

STAMMOPUR R

Revision date: 21.02.2018

No: 83007

Page 9 of 9

Relevant H and EUH statements (number and full text)

H225	Highly flammable liquid and vapour.
H302	Harmful if swallowed.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Further Information

Training instructions: Notice the directions for use on the label.

The information is based on present level of our knowledge. It does not, however, give assurances of product properties and establishes no contract legal rights.

Identified uses

No	Short title	LCS	SU	PC	PROC	ERC	AC	TF	Specification
1	STAMMOPUR R	PW	20	35	8a, 9, 13	8a	0	26	

LCS: Life cycle stages

SU: Sectors of use

PC: Product categories

PROC: Process categories

ERC: Environmental release categories

AC: Article categories

TF: Technical functions

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)