

TICKOPUR TR 7

Revision date: 28.02.2018

No: 83032

Page 1 of 9

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

TICKOPUR TR 7

1.2. Relevant identified uses of the substance or mixture and uses advised against**Use of the substance/mixture**

Cleaning agent. Universal cleaner for the ultrasonic bath, demulsifying, concentrate.

Restricted to professional users.

1.3. Details of the supplier of the safety data sheet

Company name: DR.H.STAMM GmbH Chemische Fabrik
Street: Heinrichstr. 3 – 4
Place: 12207 Berlin, GERMANY
Telephone: +49 30 76880-280
e-mail: info@dr-stamm.de
Internet: www.dr-stamm.de
Responsible Department: sdb@dr-stamm.de, Tel.: +49 30 76880-258

1.4. Emergency telephone number: 24-hours-emergency: Giftnotruf Berlin: +49 30 30686700 (german, english)

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****Regulation (EC) No. 1272/2008**

Hazard categories:

Serious eye damage/eye irritation: Eye Dam. 1

Hazard Statements:

Causes serious eye damage.

2.2. Label elements**Regulation (EC) No. 1272/2008****Hazard components for labelling**

Phosphoric acid ester, sodium-salt

C12-C14 Fatty alcohol ethoxylate

Signal word: Danger**Pictograms:****Hazard statements**

H318 Causes serious eye damage.

Precautionary statements

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

SECTION 3: Composition/information on ingredients**3.2. Mixtures**

TICKOPUR TR 7

Revision date: 28.02.2018

No: 83032

Page 2 of 9

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification according to Regulation (EC) No. 1272/2008 [CLP]			
7732-18-5	Water			60-80 %
	213-791-2			
68920-66-1	C16-C18 Fatty alcohol, ethoxylated			<8,0 %
	-		*	
111798-26-6	Phosphoric acid ester, sodium-salt			<5,0 %
	-		*	
	Skin Irrit. 2, Eye Dam. 1; H315 H318			
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol			<5,0 %
	200-661-7	603-117-00-0	01-2119457558-25	
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336			
22042-96-2	Phosphonate			<5,0 %
	244-751-4		01-2119514449-36	
112-34-5	2-(2-butoxyethoxy)ethanol, diethylene glycol monobutyl ether			<5,0 %
	203-961-6		01-2119475104-4	
	Eye Irrit. 2; H319			
68439-50-9	C12-C14 Fatty alcohol ethoxylate			<5,0 %
	-		*	
	Acute Tox. 4, Eye Dam. 1, Aquatic Chronic 3; H302 H318 H412			
497-19-8	sodium carbonate			<2,0 %
	207-838-8	011-005-00-2	01-2119485498-19	
	Eye Irrit. 2; H319			

Full text of H and EUH statements: see section 16.

Further Information

*Polymer

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Change contaminated clothing.

After inhalation

In case of inhaling spray mists, consult a doctor .

After contact with skin

After contact with skin, wash immediately with plenty of Water and soap.

After contact with eyes

Rinse immediately carefully and thoroughly with eye-bath or water. In case of troubles or persistent symptoms, consult an ophthalmologist.

After ingestion

Rinse mouth immediately and drink large quantities of water. Do not induce vomiting. Consult physician.

4.2. Most important symptoms and effects, both acute and delayed

No symptoms known up to now.

TICKOPUR TR 7

Revision date: 28.02.2018

No: 83032

Page 3 of 9

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media**

Water. Foam. Atomized water.

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

Can be released in case of fire: Nitrogen oxides (NOx). Carbon dioxide (CO2).

5.3. Advice for firefighters

Protective clothing.

Additional information

Material is not combustible. Extinguishing materials should be selected according to the surrounding area.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Wear personal protection equipment.

6.2. Environmental precautions

Do not empty into drains or the aquatic environment.

6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents).

Treat the assimilated material according to the section on waste disposal.

6.4. Reference to other sections

See protective measures under point 7 and 8.

SECTION 7: Handling and storage**7.1. Precautions for safe handling****Advice on safe handling**

No special technical protective measures are necessary.

Advice on protection against fire and explosion

Product is not: Oxidizing. Flammable. explosive.

7.2. Conditions for safe storage, including any incompatibilities**Requirements for storage rooms and vessels**

Store only in original container. Keep away from food, drink and animal feedingstuffs.

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****Occupational exposure limits**

CAS No	Substance	ppm	mg/m ³	fib/cm ³	Category	Origin
112-34-5	2-(2-Butoxyethoxy)ethanol	10	67.5		TWA (8 h)	
		15	101.2		STEL (15 min)	
67-63-0	Isopropyl alcohol	200	-		TWA (8 h)	
		400	-		STEL (15 min)	

TICKOPUR TR 7

Revision date: 28.02.2018

No: 83032

Page 4 of 9

Biological limit values

CAS No	Substance	Parameter	Value	Test material	Sampling time
67-63-0	2-Propanol	Acetone	40 mg/L	Urine	End of shift at end of workweek

DNEL/DMEL values

CAS No	Substance	DNEL type	Exposure route	Effect	Value
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol				
	Consumer DNEL, long-term	oral	systemic		26 mg/kg bw/day
	Worker DNEL, long-term	dermal	systemic		888 mg/kg bw/day
	Consumer DNEL, long-term	dermal	systemic		319 mg/kg bw/day
	Worker DNEL, long-term	inhalation	systemic		500 mg/m ³
	Consumer DNEL, long-term	inhalation	systemic		89 mg/m ³
22042-96-2	Phosphonate				
	Consumer DNEL, long-term	oral	systemic		1,9 mg/kg bw/day
	Consumer DNEL, acute	oral	systemic		1,9 mg/kg bw/day
112-34-5	2-(2-butoxyethoxy)ethanol, diethylene glycol monobutyl ether				
	Consumer DNEL, long-term	oral	systemic		1,25 mg/kg bw/day
	Worker DNEL, long-term	dermal	systemic		20 mg/kg bw/day

PNEC values

CAS No	Substance	Environmental compartment	Value
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol		
	Freshwater		140,9 mg/l
	Freshwater (intermittent releases)		140,9 mg/l
	Marine water		140,9 mg/l
	Freshwater sediment		552 mg/kg
	Marine sediment		552 mg/kg
	Soil		28 mg/kg
22042-96-2	Phosphonate		
	Freshwater		0,52 mg/l
	Marine water		0,052 mg/l
	Freshwater sediment		108 mg/kg
	Marine sediment		10,8 mg/kg
	Micro-organisms in sewage treatment plants (STP)		20 mg/l
	Soil		174 mg/kg

8.2. Exposure controls**Appropriate engineering controls**

Refer to chapter 7. No further action is necessary.

Protective and hygiene measures

Do not eat, drink, smoke or sneeze at the workplace. Wash hands before breaks and at the end of work.

Eye/face protection

Wear eye/face protection.

TICKOPUR TR 7

Revision date: 28.02.2018

No: 83032

Page 5 of 9

Hand protection

Suitable material: PE (polyethylene). CR (polychloroprenes, Chloroprene rubber). NBR (Nitrile rubber). Butyl rubber. FKM (Fluoroelastomer (Viton)).

Tested protective gloves are to be worn: EN 374

Skin protection

Skin protection: not required.

Respiratory protection

Respiratory protection not required.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Physical state:	liquid
Colour:	clear, light yellow
Odour:	characteristic

pH-Value (at 20 °C):

9,9 (conc.) 8,9 (1 %) DGF H-III 1

Test method**Changes in the physical state**

Melting point:

-8 °C

Initial boiling point and boiling range:

>100 °C

Flash point:

Explosive properties

not Explosive.

Oxidizing properties

not oxidizing.

Density (at 20 °C):

1,05 g/cm³ DIN 12791

Water solubility:

complete miscible

SECTION 10: Stability and reactivity**10.1. Reactivity**

None, in case of proper use.

10.2. Chemical stability

The product is chemically stable under normal ambient conditions.

10.3. Possibility of hazardous reactions

None, in case of proper use.

10.4. Conditions to avoid

Thermal decomposition can lead to the escape of irritating gases and vapors.

10.5. Incompatible materials

Oxidizing agents, strong.

10.6. Hazardous decomposition products

None, in case of proper use.

Further information

Do not mix with other products.

SECTION 11: Toxicological information**11.1. Information on toxicological effects****Acute toxicity**

Based on available data, the classification criteria are not met.

TICKOPUR TR 7

Revision date: 28.02.2018

No: 83032

Page 6 of 9

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
68920-66-1	C16-C18 Fatty alcohol, ethoxylated				
	oral	LD50 >2000 mg/kg	Ratte		
111798-26-6	Phosphoric acid ester, sodium-salt				
	oral	LD50 >2000 mg/kg	Ratte		
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol				
	oral	LD50 4750 mg/kg	rat		OECD 401
	dermal	LD50 12800 mg/kg	kan		OECD 402
	inhalative (4 h) vapour	LC50 >25 mg/l	rat		OECD 403
22042-96-2	Phosphonate				
	oral	LD50 >5000 mg/kg	Ratte		
	dermal	LD50 >5000 mg/kg	Kaninchen		
112-34-5	2-(2-butoxyethoxy)ethanol, diethylene glycol monobutyl ether				
	oral	LD50 3305 mg/kg	rat		
	dermal	LD50 2764 mg/kg	rabbit		
68439-50-9	C12-C14 Fatty alcohol ethoxylate				
	oral	LD50 >2000 mg/kg	rat		Cesio-Recommendation
497-19-8	sodium carbonate				
	oral	LD50 4090 mg/kg	Rat	IUCLID	

Irritation and corrosivity

Causes serious eye damage.

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Risk of serious damage to eyes.

Sensitising effects

Based on available data, the classification criteria are not met.

no danger of sensitization.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

SECTION 12: Ecological information**12.1. Toxicity**

Technically correct releases of minimal concentrations to adapted biological sewage treatment facility, will not disturb the biodegradability of activated sludge.

TICKOPUR TR 7

Revision date: 28.02.2018

No: 83032

Page 7 of 9

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
68920-66-1	C16-C18 Fatty alcohol, ethoxylated					
	Acute fish toxicity	LC50	30 mg/l	96 h		
	Acute crustacea toxicity	EC50 mg/l	>1000	48 h		
111798-26-6	Phosphoric acid ester, sodium-salt					
	Acute fish toxicity	LC50	>10 mg/l	96 h		
	Acute crustacea toxicity	EC50 mg/l	>100	48 h	Daphnia magna	
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol					
	Acute fish toxicity	LC50 mg/l	>100	96 h		
	Acute bacteria toxicity	(>100 mg/l)				
68439-50-9	C12-C14 Fatty alcohol ethoxylate					
	Algae toxicity	NOEC	<1 mg/l			
497-19-8	sodium carbonate					
	Acute fish toxicity	LC50	300 mg/l	96 h	Lepomis macrochirus	
	Acute crustacea toxicity	EC50	265 mg/l	48 h	Daphnia magna	IUCLID

12.2. Persistence and degradability

The surfactants contained in this preparation comply with the biodegradability criteria as laid down in Regulation (EC) No.648/2004 on detergents. Data to support this assertion are held at the disposal of the competent authorities of the Member States and will be made available to them, at their direct request or at the request of a detergent manufacturer.

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
68920-66-1	C16-C18 Fatty alcohol, ethoxylated			
	OECD 301D	>70 %	28	
	Leicht biologisch abbaubar			
68439-50-9	C12-C14 Fatty alcohol ethoxylate			
	OECD 301F	>60 %	28	
	easily biodegradable			

12.3. Bioaccumulative potential

On the basis of existing data about disposal/decomposition and bio-accumulation potential, long term environmental damage is unlikely.

BCF

CAS No	Chemical name	BCF	Species	Source
112-34-5	2-(2-butoxyethoxy)ethanol, diethylene glycol monobutyl ether	<100		

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

not applicable

12.6. Other adverse effects

No data available

SECTION 13: Disposal considerations**13.1. Waste treatment methods**

TICKOPUR TR 7

Revision date: 28.02.2018

No: 83032

Page 8 of 9

Advice on disposal

According to EAKV, allocation of waste identity numbers/waste descriptions must be carried out in a specific way for every industry and process.

Waste disposal number of waste from residues/unused products

200129 MUNICIPAL WASTES (HOUSEHOLD WASTE AND SIMILAR COMMERCIAL, INDUSTRIAL AND INSTITUTIONAL WASTES) INCLUDING SEPARATELY COLLECTED FRACTIONS; separately collected fractions (except 15 01); detergents containing hazardous substances; hazardous waste

Waste disposal number of used product

200129 MUNICIPAL WASTES (HOUSEHOLD WASTE AND SIMILAR COMMERCIAL, INDUSTRIAL AND INSTITUTIONAL WASTES) INCLUDING SEPARATELY COLLECTED FRACTIONS; separately collected fractions (except 15 01); detergents containing hazardous substances; hazardous waste

Contaminated packaging

Completely emptied packings can be re-cycled.

SECTION 14: Transport information**Other applicable information**

Not a hazardous material with respect to transportation regulations.

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 55: 2-(2-butoxyethoxy)ethanol, diethylene glycol monobutyl ether

2004/42/EC (VOC): 6,2 % (65,1 g/l)

National regulatory information

Water contaminating class (D): 1 - slightly water contaminating

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information**Changes**

Data changed from previous versions: 2.1., 3.2., 8.1., 9.1., 11.1., 12.1., 12.2., 13.1., 15.1., 16.

Classification for mixtures and used evaluation method according to Regulation (EC) No. 1272/2008 [CLP]

Classification	Classification procedure
Eye Dam. 1; H318	Calculation method

Relevant H and EUH statements (number and full text)

H225 Highly flammable liquid and vapour.
 H302 Harmful if swallowed.
 H315 Causes skin irritation.
 H318 Causes serious eye damage.
 H319 Causes serious eye irritation.
 H336 May cause drowsiness or dizziness.
 H412 Harmful to aquatic life with long lasting effects.

Further Information

Training instructions: Notice the directions for use on the label.

The information is based on present level of our knowledge. It does not, however, give assurances of product properties and establishes no contract legal rights.

TICKOPUR TR 7

Revision date: 28.02.2018

No: 83032

Page 9 of 9

Identified uses

No	Short title	LCS	SU	PC	PROC	ERC	AC	TF	Specification
1	TICKOPUR TR 7	IS, PW, C	0	35	8a, 9, 13	8a	0	26	

LCS: Life cycle stages

PC: Product categories

ERC: Environmental release categories

TF: Technical functions

SU: Sectors of use

PROC: Process categories

AC: Article categories

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)